



Soil characterization using electrical resistivity tomography and geotechnical investigations

Kumari Sudha^{a,*}, M. Israil^{b,1}, S. Mittal^c, J. Rai^a

^a Department of Physics, Indian Institute of Technology Roorkee, Roorkee-247667, India

^b Department of Earth Sciences, Indian Institute of Technology Roorkee, Roorkee-247667, India

^c Department of Civil Engineering, Indian Institute of Technology Roorkee, Roorkee- 247667, India

ARTICLE INFO

Article history:

Received 12 September 2007

Accepted 22 September 2008

Keywords:

Electrical resistivity tomography

Transverse resistance

Geotechnical tests

Standard penetration test

Dynamic cone penetration test

ABSTRACT

Electrical Resistivity Tomography (ERT) has been used in association with Standard Penetration Test (SPT) and Dynamic Cone Penetration Test (DCPT) for Geotechnical investigations at two sites, proposed for thermal power plants, in Uttar Pradesh (UP), India. SPT and DCPT tests were conducted at 28 points and two ERT profiles, each measuring 355 m long, were recorded using 72 electrodes deployed at 5 m spacing. Electrical characterization of subsurface soil was done using borehole data and grain size analysis of the soil samples collected from boreholes. The concept of electrical resistivity variation with soil strength related to the grain size distribution, cementation, porosity and saturation has been used to correlate the transverse resistance of soil with the number of blow counts (N -values) obtained from SPT and DCPT data. It was thus observed that the transverse resistance of soil column is linearly related with the number of blow counts (N -values) at these sites. The linear relationships are site-specific and the coefficients of linear relation are sensitive to the lithology of subsurface formation, which was verified by borehole data. The study demonstrates the usefulness of the ERT method in geotechnical investigations, which is economic, efficient and less time consuming in comparison to the other geotechnical methods, such as SPT and DCPT, used for the purpose.

© 2008 Elsevier B.V. All rights reserved.

1. Introduction

Characterization of subsurface soil and determination of soil strength are prerequisite for the foundation design of important civil engineering structures. Electrical characterization of soil was done by conducting surface electrical resistivity measurements and subsequently translating these data in terms of electrical properties of subsurface soil (Israil and Pachauri, 2003). Various attempts have been made in literatures to integrate the ERT and geotechnical data for characterization of subsurface soil (Cosenza et al., 2006; Gay et al., 2006). The application of electrical resistivity for characterization of soil was reviewed by Samouëlian et al., (2005).

Alternatively, in geotechnical studies, Standard Penetration Test (SPT) furnishes data about the resistance of soils to penetration, which can be used to evaluate the soil strength in terms of number of blows (N -values). The N -values are defined as the number of blows per 30 cm of penetration into the soil. Following the procedure of IS 6403 - (1981) code, N -values can be used to obtain the bearing capacity of soils. In Dynamic Cone Penetration Test (DCPT), the resistance, N -value, to penetration of the cone in terms of the num-

ber of blows per 30 cm of penetration is correlated with the bearing capacity of the soil. The data from these geotechnical tests (SPT and DCPT) in association with the borehole data and laboratory measurement of soil properties (e.g., grain size distribution, degree of saturation and permeability) are used to characterize the subsurface soil.

Geotechnical tests are time-consuming and expensive. On the other hand, geoelectrical methods are faster and comparatively cheap. The use of Electrical Resistivity Tomography (ERT) technique provides the electrical image of subsurface soil and has become an important tool for the electrical characterization of soil. Correlation between electrical parameters and soil strength, derived from geotechnical tests, can be studied by choosing different electrical parameters. It has been reported in literature (Braga et al., 1999; Giao et al., 2003) that the relationship between the electrical parameters such as chargeability, resistivity and N -values is poor.

The physics of electrical current flow in the subsurface soil suggests that the possible relationship between the soil strength and electrical resistivity should be based on the parameters which control soil strength as well as electrical resistivity such as grain size distribution, degree of saturation, porosity and cementation. It is so since resistivity is sensitive to the salinity of saturating fluid whereas soil strength is not related with it. Therefore, the relationship between electrical parameters and soil strength will be meaningless if the salinity of saturating fluid changes with depth. On the other hand, clay content in soil matrix can affect both soil strength as well as its

* Corresponding author.

E-mail addresses: sudha_gupta00@yahoo.co.in (K. Sudha), mohdfes@iitr.ernet.in (M. Israil).

¹ Tel.: +91 1332 285078; fax: +91 1332 273560.